SAFETY DATA SHEET



Electron Capture Detector Sample, Part Number 5183-0379

Section 1. Identification

1.1 Product identifier

Product name : Electron Capture Detector Sample, Part Number 5183-0379

Part no. : 5183-0379 **Validation date** : 5/21/2018

1.2 Relevant identified uses of the substance or mixture and uses advised against

Material uses : Reagents and Standards for Analytical Chemistry Laboratory Use

5183-0379-1 Electron Capture Detector Sample 3 x 0.5 ml

1.3 Details of the supplier of the safety data sheet

Supplier/Manufacturer: Agilent Technologies, Inc.

5301 Stevens Creek Blvd Santa Clara, CA 95051, USA

800-227-9770

1.4 Emergency telephone number

In case of emergency : CHEMTREC®: 1-800-424-9300

Section 2. Hazards identification

2.1 Classification of the substance or mixture

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Classification of the substance or mixture

FLAMMABLE LIQUIDS - Category 2
H315 SKIN IRRITATION - Category 2
H319 EYE IRRITATION - Category 2A

H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract

irritation) - Category 3

H336 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) -

Category 3

H304 ASPIRATION HAZARD - Category 1 H400 AQUATIC HAZARD (ACUTE) - Category 1 H410 AQUATIC HAZARD (LONG-TERM) - Category 1

2.2 GHS label elements

Hazard pictograms









Signal word : Danger

Hazard statements : ₩225 - Highly flammable liquid and vapor.

H319 - Causes serious eve irritation.

H315 - Causes skin irritation.

H304 - May be fatal if swallowed and enters airways.

H335 - May cause respiratory irritation. H336 - May cause drowsiness or dizziness.

H410 - Very toxic to aquatic life with long lasting effects.

Date of issue: 05/21/2018 **1/13**

Section 2. Hazards identification

Precautionary statements

Prevention

: P280 - Wear protective gloves. Wear eye or face protection.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 - Use explosion-proof electrical, ventilating, lighting and all material-handling equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P233 - Keep container tightly closed.

P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P261 - Avoid breathing vapor.

P264 - Wash hands thoroughly after handling.

Response

: P391 - Collect spillage.

P304 + P340 + P312 - IF INHALED: Remove person to fresh air and keep comfortable

for breathing. Call a POISON CENTER or physician if you feel unwell.

P301 + P310 + P331 - IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting.

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P302 + P352 + P362+P364 - IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse.

P332 + P313 - If skin irritation occurs: Get medical attention.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical attention.

Storage

: P405 - Store locked up.

P403 - Store in a well-ventilated place.

P235 - Keep cool.

Disposal

: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

2.3 Other hazards

Hazards not otherwise classified

ciassified

: None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	%	CAS number
2,2,4-trimethylpentane	≥90	540-84-1

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Date of issue: 05/21/2018 **2/13**

Section 4. First aid measures

4.1 Description of necessary first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

4.2 Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or

dizziness. May cause respiratory irritation.

Skin contact : Causes skin irritation.

Ingestion: Can cause central nervous system (CNS) depression. May be fatal if swallowed and

enters airways.

Over-exposure signs/symptoms

Eye contact: Adverse symptoms may include the following:

pain or irritation

watering redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

nausea or vomiting

headache

drowsiness/fatigue dizziness/vertigo unconsciousness

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion: Adverse symptoms may include the following:

nausea or vomiting

Date of issue: 05/21/2018 3/13

Section 4. First aid measures

4.3 Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments

: No specific treatment.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

: Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media

: Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards arising from the chemical

: Mighly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

Decomposition products may include the following materials: carbon dioxide carbon monoxide

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Date of issue: 05/21/2018 4/13

Section 6. Accidental release measures

6.2 Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

7.1 Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Do not swallow. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations : Industrial applications, Professional applications.

Industrial sector specific

: Not applicable.

solutions

Section 8. Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Ingredient name	Exposure limits	
2,2,4-trimethylpentane	ACGIH TLV (United States, 3/2017). TWA: 300 ppm 8 hours.	

8.2 Exposure controls

Date of issue: 05/21/2018 5/13

Section 8. Exposure controls/personal protection

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear antistatic protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid.

Color : Clear. Colorless.

Odor : Gasoline-like

Odor threshold : Not available.

pH : Not available.

Melting point : -107°C (-160.6°F)

Boiling point : 99.2°C (210.6°F)

Flash point : Closed cup: -14°C (6.8°F) Open cup: 4.5°C (40.1°F)

Date of issue: 05/21/2018 6/13

Section 9. Physical and chemical properties

Evaporation rate : Not available.
Flammability (solid, gas) : Not applicable.
Lower and upper explosive : Lower: 1.1%

(flammable) limits Upper: 6%

Vapor pressure : 5.5 kPa (41 mm Hg) [room temperature]

Vapor density : 3.93 [Air = 1]
Relative density : Not available.

Solubility : Insoluble in the following materials: cold water and hot water.

Partition coefficient: n-

octanol/water

: Not available.

Auto-ignition temperature : 418°C (784.4°F)

Decomposition temperature : Not available.

Viscosity : Not available.

Section 10. Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld,

braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not

allow vapor to accumulate in low or confined areas.

10.5 Incompatible materials : Reactive or incompatible with the following materials:

oxidizing materials

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2,2,4-trimethylpentane	LC50 Inhalation Vapor LD50 Oral	Female	>33.52 mg/l >5000 mg/kg	4 hours

Irritation/Corrosion

Not available.

Conclusion/Summary

Skin : Repeated exposure may cause skin dryness or cracking.

Sensitization

Not available.

Mutagenicity

Date of issue: 05/21/2018 **7/13**

Section 11. Toxicological information

Conclusion/Summary

: Not available.

Carcinogenicity

Conclusion/Summary

: Not available.

Reproductive toxicity

Conclusion/Summary

: Not available.

Teratogenicity

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
2,2,4-trimethylpentane	Category 3		Respiratory tract irritation and Narcotic effects

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Name	Result
· · · · · · · · · · · · · · · · · · ·	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure

: Routes of entry anticipated: Oral, Dermal, Inhalation.

Potential acute health effects

Eye contact

: Causes serious eye irritation.

Inhalation

: Can cause central nervous system (CNS) depression. May cause drowsiness or

dizziness. May cause respiratory irritation.

Skin contact

: Causes skin irritation.

Ingestion

: Can cause central nervous system (CNS) depression. May be fatal if swallowed and

enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact

: Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation

: Adverse symptoms may include the following:

respiratory tract irritation

coughing

nausea or vomiting

headache

drowsiness/fatigue dizziness/vertigo unconsciousness

Skin contact

: Adverse symptoms may include the following:

irritation redness

Ingestion

: Adverse symptoms may include the following:

nausea or vomiting

Date of issue: 05/21/2018 8/13

Section 11. Toxicological information

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.
 Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
2,2,4-trimethylpentane	Acute LC50 0.11 mg/l Fresh water	Fish	96 hours

12.2 Persistence and degradability

Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2,2,4-trimethylpentane	4.08	231	low

12.4 Mobility in soil

Soil/water partition : Not available. coefficient (Koc)

12.5 Other adverse effects : No known significant effects or critical hazards.

Date of issue: 05/21/2018 **9/13**

Section 13. Disposal considerations

13.1 Waste treatment methods

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

The information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

Section 14. Transport information

DOT / TDG / Mexico / IMDG / : Not regulated.

IATA

Additional information

Remarks: De minimis quantities

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in the

event of an accident or spillage.

Transport in bulk according: Not available. to Annex II of MARPOL and

the IBC Code

Section 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

U.S. Federal regulations : TSCA 8(a) CDR Exempt/Partial exemption: Not determined

> Clean Water Act (CWA) 307: Gamma-HCH or gamma-BHC Clean Water Act (CWA) 311: Gamma-HCH or gamma-BHC

Clean Air Act Section 112 Listed

(b) Hazardous Air **Pollutants (HAPs)**

Clean Air Act Section 602

Class I Substances

: Not listed

Date of issue: 05/21/2018 10/13

Section 15. Regulatory information

Clean Air Act Section 602

Class II Substances

: Not listed

DEA List I Chamicals

DEA List I Chemicals (Precursor Chemicals)

: Not listed

DEA List II Chemicals (Essential Chemicals)

: Not listed

SARA 302/304

Composition/information on ingredients

			SARA 302 TPQ		SARA 304 RQ	
Name	%	EHS	(lbs)	(gallons)	(lbs)	(gallons)
Samma-HCH or gamma-BHC	<0.0001	Yes.	1000 / 10000	-	1	-

SARA 304 RQ : 20920502.1 lbs / 9497907.9 kg

SARA 311/312

Classification : FLAMMABLE LIQUIDS - Category 2

SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract

irritation) - Category 3

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) -

Category 3

ASPIRATION HAZARD - Category 1

Composition/information on ingredients

Name	%	Classification
2,2,4-trimethylpentane	≥90	FLAMMABLE LIQUIDS - Category 2 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 ASPIRATION HAZARD - Category 1 HNOC - Defatting irritant

State regulations

Massachusetts : The following components are listed: ISOOCTANE

New York : The following components are listed: 2,2,4-Trimethylpentane

New Jersey : The following components are listed: ISOOCTANE; 2,2,4-TRIMETHYLPENTANE

Pennsylvania : The following components are listed: PENTANE, 2,2,4-TRIMETHYL-

California Prop. 65

MARNING: This product can expose you to Hexachlorocyclohexane (gamma isomer), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	level	Maximum acceptable dosage level
⊮exachlorocyclohexane (gamma isomer)	Yes.	-

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Date of issue: 05/21/2018 **11/13**

Section 15. Regulatory information

Montreal Protocol (Annexes A, B, C, E)

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia : All components are listed or exempted.

Canada : All components are listed or exempted.

China : All components are listed or exempted.

Europe : All components are listed or exempted.

Japan : Japan inventory (ENCS): All components are listed or exempted.

Japan inventory (ISHL): All components are listed or exempted.

Malaysia : Not determined.

New Zealand : Not determined.

Philippines : All components are listed or exempted.

Republic of Korea : All components are listed or exempted.

Taiwan : All components are listed or exempted.

Thailand : Not determined.

Turkey : Not determined.

United States : All components are listed or exempted.

Viet Nam : Not determined.

Section 16. Other information

History

Date of issue: 05/21/2018Date of previous issue: 06/09/2016

Version : 7

Procedure used to derive the classification

Classification	Justification
AMMABLE LIQUIDS - Category 2	On basis of test data
SKIN IRRITATION - Category 2	Calculation method
EYE IRRITATION - Category 2A	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract	Calculation method
irritation) - Category 3	
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) -	Calculation method
Category 3	
ASPIRATION HAZARD - Category 1	Expert judgment
AQUATIC HAZARD (ACUTE) - Category 1	Calculation method
AQUATIC HAZARD (LONG-TERM) - Category 1	Calculation method

[▼] Indicates information that has changed from previously issued version.

Notice to reader

Date of issue: 05/21/2018 **12/13**

Electron Capture Detector Sample, Part Number 5183-0379

Section 16. Other information

Disclaimer: The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

Date of issue: 05/21/2018 **13/13**